ORDER FORM

TT Definitive Socket

Date: MM.DD.YYYY

| CUSTOMER INFORM | IATION | | | | |
|--|---|--|---|--|--|
| Clinician Name: | | Facility/Clinic: | | | |
| Preferred Contact Method: | | Bill to Account #: | PO # | # : | |
| O Phone: | | Shipping Address Line | e 1: | | |
| O Email Address: | | Shipping Address Line 2: | | | |
| SHIPPING AND PATI | ENT INFORMATION | | | | |
| Carrier: Method: | | Patient ID/Last Name: | | | |
| ○ UPS○ Ground○ 3 - Day○ 2 - Day○ FedEx○ Next Day○ Next Day Saver | | Height: ft in K-Level: | | | |
| | | Weight: lbs O K1 O K3 | | | |
| Amputation Side: | Amputation Level: | Foot Size: | cm | 2 O K4 | |
| O Left O Bilateral *Requires separate order forms | ○ TT ○ Symes | | | | |
| Right Indicate side on each form. | 5. | | | | |
| PRODUCT INFORMA | TION (The diagnostic soc | cket must be the final modified ve | rsion, in dynamic alignmen | t to proceed) | |
| Measurements: | SOCKET MATERIAL | SOCKET FINISH | INSERT OPTIONS | PROSTHETIC HEIGHT | |
| ○ cm ○ in | (select several) O Polypropylene | (select one) Carbon Finish | (select one) | (select several) | |
| | Copolymer Cs-DSTT-201 | PRS SkinTone | No Insert Polyethylene | O Transfer As Is | |
| | Carbon from Cast | O Light PRS #3 | CS-DSAD-260 | ○ Shorten | |
| MP to Floor | CS-DSTT-202 Carbon from CAD | O Medium PRS #6 | O Proflex (w/silicone) CS-DSAD-261 | O Extend | |
| | CS-DSTT-203 | O DarkPRS #13 O Other PRS Color # | OP-TEK Flex Black cs-dsAd-262 | O cm O in | |
| | SOCKET OPTIONS | | OP-TEK Flex Natural | VALVE OPTIONS (select several) | |
| Calf to Floor Largest Ca | If (select several) | Decorative Lamination | CS-DSAD-263 | O No Valve | |
| | O Symes Door | Customer Supplied Fabric CS-DSAD-481 Other PRS Color # | O Orfit x-Soft (w/silicone) CS-DSAD-264 | | |
| | Exoskeletal Lamination | O Dark PRS #13 | O Pelite Liner CS-DSAD-460 | O Customer Supplied Valve CS-DSAD-440 | |
| | CS-DSAD-290 | O WW Laminating Sleeve | O Keasy Cone Liner | O Pushbutton Lyn BK2 Valve CS-DSAD-442 | |
| Largest Ank | Install & ShapeTT Foam Cover | Fred's Legs Design Name | CS-DSAD-461 O Molded Distal Cushion | O V4 Easy Line Valve (4R136) | |
| | CS-DSAD-290 | fredslegs.com/collections/laminating | CS-DSAD-462 | CS-DSAD-444 | |
| LOCK OPTIONS (select several) | | MOUNTING PLATE OPTIONS (select several) | | | |
| ○ No Lock | ○ Genesis Bulldog Lock | O No Plate | WWSS3-Prong | | |
| O Add space forlock CS-DSAD-420 | (3GEN-A) CS-DSAD-425 | Customer Supplied Plate | | | |
| Type: O Fillauer Shuttle Lock (125234) | | CS-DSAD-401 | O Prong only (FND- CS-DSAD-404 | Prong only (FND-268002) CS-DSAD-404 | |
| O Customer Supplied Lock CS-DSAD-421 | (CS-DSAD-426) | CS-DSAD-403 | | I M I B | |
| O Coyote Air-Lock+Alignable Connector+DirectionInsert CS-DSAD-423 | O Fillauer- Nut Only (809732) CS-DSAD-427 | O Prong + Rotatable Male Pyramid (FND-268001) O Bulldog FHLA - 10 CS-DSAD-408 CS-DSAD-405 | | | |
| Coyote Air-Lock (CD103) CS-DSAD-424+CS-DSAD-401 to 408 | O Alpha Lock (700-AIS480) CS-DSAD-432 | O WW Gray Attachment Block (700-250) O Prong+ Rotatable CS-DSAD-402 CS-DSAD-406 | | le Female Receiver (FND-268000) | |
| Notes: | | DRAW WINDOW(S) & DIAL(S) POSITIONON TEST SOCKET (select several) | | | |
| | RevoLock ® I | | Scient Several j | RevoFit ® | |
| | | ace O Additional Dial &Lace | Additional Window(s) | ○ 1 Dial, 1 Lace, 1 Window | |
| | CS-DSAD-48 | 5 CS-DSAD-483 (Total Qty 2) | CS-DSAD-484 Qty | CS-DSAD-483 (Qty 1) | |