

FiberGlass META Core[™]









Transtibial

PDAC Approved L-Code: L5981

Product Highlights

- Boltless, unibody fiberglass platform
- Greater than 90% dynamic energy return at the toe and heel
- Split keel design
- Corrosion resistant and waterproof
- Low build height

The FiberGlass META Core foot delivers the full benefits of the META-Unibody® platform in fiberglass for low activity K3 to high activity K4 prosthetic users up to 365 lbs. This patent pending breakthrough features a single piece of fiberglass, which is free of wraps and hardware to reduce weight while maximizing dynamic response.

The split keel design and compliant, durable composite provides users improved stability while delivering natural roll-over across terrains and environments.


FiberGlass META Core Foot: Specifications

Heel Height: 10 mm (3/8")

Build Height: 105 mm (4.13")

Approximate Product Weight: 655 g *Std. size 26 Cat. 5 with foot shell and sock

Trial Period: 60 days from date of patient fitting



FiberGlass META Core Build Height 105 mm (4.13")

Heel Height 10 mm (3/8")

Sandal Toe Foot Shells







Buff

FiberGlass META Core Category Chart

Standard (Low to Medium) Impact Level

High Impact Level

Adjusted User Weight (patient body weight + loads carried)	Sizes 22-24 cm	Sizes 25-30 cm	Sizes 22-24 cm	Sizes 25-30 cm
99-115 lbs (45-51 kg)	1	1	1	1
116-130 lbs (52-58 kg)	1	1	2	2
131-150 lbs (59-67 kg)	2	2	3	3
151-170 lbs (68-76 kg)	3	3	4	4
171-194 lbs (77-87 kg)	4	4	5	5
195-221 lbs (88-99 kg)	5	5	-	6
222-256 lbs (100-115 kg)	-	6	-	7
257-287 lbs (116-130 kg)	-	7	-	8
288-324 lbs (131-147 kg)	-	8	-	9
325-365 lbs (148-165 kg)	-	9	-	-

^{*}Note: The Standard impact level is recommended for most patients for day-to-day use; high impact level should be chosen for active outdoor users engaged in activities that involve heavy ground impact forces (e.g. sports, construction work)

The META Lineup

All META feet feature the groundbreaking META-Unibody® design that combines dynamic response with lightweight, hardware-free design suitable for K3-K4 users. The design delivers a smooth roll-over experience and delivers support in mid-terminal stance enhancing stability without compromising function.



META Core

Smooth rollover and latestance support for K3-K4 users low-build height and weight.

Available in Carbon Fiber or Fiberglass.*

PDAC approved: L5981



META Arc

Biomimetic ankle offers stability and adaptation to terrain. 20° of inversion & eversion.

PDAC approved: L5981 + L5986



META Shock

Adaptive shock absorption via integrated shock module 13 mm of vertical displacement.

PDAC approved: L5987



META Shock X

Adaptive shock absorption and impact protection via 40° of torsional rotation + 13 mm vertical displacement.

Available in Carbon Fiber or Fiberglass.*

PDAC approved: L5987 + L5984

How To Order

